



# Shield Products

Residential / Commercial / Industrial  
Sealers and Protective Coatings



## SUPERIOR SHIELD RADIANT BARRIER INSULATOR

Application instructions- asphalt shingles, Tile, concrete or Metal roofs.

### Step #1

Make repairs as necessary, Substrate must be perfectly dry, do not go over a ten on a moisture meter. Notify customer of any extra charges for repairs prior to work.

### Step #2

Pressure wash complete area at low pressure (Approx 600 PSI) Use Super Shield Anti Microbial Cleaner (SKU50800). If applying directly to surface do in sections so it does not dry on you before you clean. Rinse clean after this process. Make sure surface is dry before applying Superior Shield or any coating. Normally 4-6 hours dry time in the sun. Test before coating. Don't leave foot prints

### Step #3

Apply 20 mils of Mastishield clear or white, allow 6-8 hours to dry. Must be able to walk on it with no prints.

**SHIELD PRODUCTS WILL NOT HONOR WARRANTY OR ASSUME ANY RESPONSIBILITY FOR DAMAGE IF CHLORINE IS USED PRIOR TO COATING.**

### Step #4

Apply one coat Superior Shield SKU20059VCR20- 3-5 Mil wet for residential Shingles –Clay or concrete tiles or metal roofs. Should be sprayed. Dry time subject to sun, heat & Humidity, For walk on approx four to eight hours.. Rain should not effect after 3 -4 hour.

////////////////////////////////////

**Important Notes:** Recommended tip size. 523 for airless equipment or equivalent. Tip can be larger if necessary. Remove all filters. Watch for wear on tip as ceramics will wear, increase flow and change coverage and cost. You may have to replace this at least once.

**Energy Saving Material may rise to top of container, Make sure the material is thoroughly mixed back in before using.**

Disclaimer: It is the responsibility of the Applicator or purchaser to determine the compatibility of the substrate that Shield Products are applied to and any regulations that may apply in the area. We will provide information to the best of our ability but will not warrant or be held responsible for results which we have no control over. We warrant our products fully warranted as described in company published warranty.

**WE ARE GREEN**

SHIELD PRODUCTS JACKSONVILLE, FL  
Sales 904-732-7044- Plant-fax-904 732 7009 FAX-904 645 6155

[www.shieldproducts.com](http://www.shieldproducts.com) E-Mail [shieldproducts@comcast.net](mailto:shieldproducts@comcast.net)