

# FLUOROBLEND WATER-BASE TOP COAT OR PRIMER SKU-66070

## DESCRIPTION:

Fluoroblend Blend single component, self cross linking coating, formulated to provide the ultimate in resistance to weathering and ultraviolet degradation with unsurpassed gloss retention. Coating will retain its appearance over an expected life of 12 years in even the most aggressive environments. Very economical to use on buildings, floors and many other areas either as a primer or top coat. VOC Compliant, Non Flammable, Anti Microbial.

## RECOMMENDED USES:

Fluoroblend can be used as a shop field applied top coat for prepared concrete, glass, fiberglass, vinyl or plastic surfaces where the very best appearance retention and wear is required. Non-slip available, post add colors.

## FEATURES:

Fluoroblend is available in satin or gloss finish. It is made up of a blend of Fluoropolymer & Acrylic. It has automotive quality finish. You can spray, or roll Fluoroblend SKU66070 and will cover up to 800 sq ft per gal

## APPLICATION:

Fluoroblend SKU66070 TOP COAT or a PRIMER COAT

Top coat two coats- Approx 4 Plus mils wet, 2-3 mils dry. Primer, One coat roll, spray.

## DRYING TIME@72°F

- 1.Dry to the touch (30 MIN TO 1 hour)
- 2.Dry to handle (1-2 hours)
- 3.Dry to traffic (12-24 hours hours)

## CURE TIME:

Approximately 12-24 hours subject to heat & humidity

## Characteristics:

<b>Wet Film Thickness</b>	<b>4-6 mils</b>	<b>Dry time 15-30 Min</b>
<b>Dry Film Thickness Range</b>	<b>2-3 mils</b>	<b>Temp range: 50F Min-90F max</b>
<b>Relative Humidity</b>	<b>90% Maximum</b>	<b>Substrate Temp: 80F-100 F</b>
<b>Dew Point</b>	<b>+ 5F</b>	<b>Wgt per Gl: 8.1 lb</b>
<b>Minimum Surface Prep</b>	<b>Clean &amp; Dry</b>	<b>Non Flammable</b>

Shelf Life: 12 months-Keep covered