

**SHIELD PRODUCTS****FLUOROSEAL/ACRYLIC/URETHANE/FLUOROPOLYMER PRIMER**

SKU50806 SOLVENT-BASE

**DESCRIPTION:**

FLUOROSEAL single component, formulated to provide the ultimate in adhesion, will retain protection in even the most aggressive environments. Very economical to use on buildings, floors and many other areas as a primer.

**RECOMMENDED USES:**

Fluoroseal can be used as a shop or field applied primer for concrete, glass, fiberglass, vinyl, metal, wood or plastic surfaces where the very best protection retention and wear is required.

**FEATURES:**

Fluoroseal is available in clear or color. Grey, Black, White or Red Oxide. It is made up of a blend of Fluoropolymer, Acrylic & URETHANE. It has a tough durable finish. You can spray, brush or roll. Fluoroseal SKU 50806 will cover up to 600 sq ft per gal @ 3 mils wet.

**APPLICATION: Fluoroseal SKU50806**

One coat, Approx 3-4 mils wet-total, 1-1/2 mils dry.

Brush, roll, spray.

**DRYING TIME@72°F**

1. Dry to the touch (30 MIN TO 1 hour)
2. Dry to handle (1-2 hours)
3. Dry to traffic (4-12 hours)

**TOTAL CURE TIME:** Approximately 72 hours subject to heat & humidity

**Characteristics:**

Wet Film Thickness: Range	3-4 mils	
Dry Film Thickness: Range:	1.5-2 Mils	Temp range: Min 40°F max-90°F
Relative Humidity:	90% Maximum	Substrate Temp: 80°-100° F
Wgt per Gl: 8.1 lb		
Minimum Surface Prep:	Clean & Dry	
Coverage 500-600 sq ft	Shelf Life: 24 months	

Tel 1-904 880-6860 Fax 1-904 645 6155

[shieldproducts@comcast.net](mailto:shieldproducts@comcast.net) web- [www.shieldproducts.com](http://www.shieldproducts.com)